

PRESSALIT.

Pressalit Projecta D Solid Pro without cover 1005 Standard toilet seat without cover with Polygiene® incl. Solid Pro hinge

Item number 1005011-DG4925

NRF:6190286

EAN:5708590345413

Pressalit Projecta D Solid Pro - without cover. D-shaped seat, which is well suited to the project market. With an antibacterial Polygiene effect. Harmonious design, ultimate strength and sturdy fittings with optimum

stability - even during sideways transfer.

Colour

Description

PRESSALIT toilet seat without cover, model "Projecta
D Solid Pro", art.no. 1005 made of colour ingrained
duroplast with polygiene incl. DG4 combi hinge,


universal.

White


- centre distance: 145-210 mm

- load - ring seat 240 kg

- 10 year guarantee







Design type Sandwich

Designer Pressalit

Design year 2016



PRESSALIT.

Pressalit Projecta D Solid Pro without cover 1005 Standard toilet seat without cover with Polygiene® incl. Solid Pro hinge

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

BUFFERS:

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M, thermoplastic semi-crystalline polyamides with partially aromatic content. Aluminium profile EN AW-6063-TS.

Product capacity Load - ring seat 240 kg

Weight 1,534 kg

Carton size 490x389x84 mm

Gross weight 1,874 kg

Crate size 517x399x456 mm

Weight per crate 9,37 kg

Qty per crate 5

Crates per pallet 8

Qty per pallet 40

Cleaning

Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make

sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.



PRESSALIT.

Pressalit Projecta D Solid Pro without cover 1005 Standard toilet seat without cover with Polygiene® incl. Solid Pro hinge

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

| Strip |

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

PRESSALIT: